

Proxima Ovation+ 846 Projection Panel

Technical and Functional Specifications

What's included	• LCD Projection Panel
	• PC Video Cable
	• Macintosh Video Cable
	• Composite Audio/Visual Cable
	• Programmable Remote Control
	• Power Supply and I.E.C. Power Cord
	• User's Manual
Computer Compatibility	• Deluxe Soft Dust Cover
	• Registration Bonus: Presentation Control Software
	• IBM PC, PS/2 and compatibles
	• Olivetti/AT&T
Video Resolution Supported	• NEC 9801
	• Apple Macintosh II Family, LC, Quadra, Centris, Performa, Power Macintosh, and PowerBook families
	• Computer video modes up to 800 x 600 at 56 Hz, including VESA 640 x 480 up to 72 Hz
	• NTSC M 3.58 MHz
Video Compatibility	• PAL G, B, H, I 4.42 MHz
	• SECAM 4.43 MHz
H-Sync Range	• 15 to 40 KHz
V-Sync Range	• 50 to 75 KHz
Interface Connectors	• From computer: D825
	• To monitor: DB25 and HD15
	• Serial: Full duplex with Mini DIN-8 and DB9
LCD Panel	• Video: RCA composite and 4 pin Mini DIN S-VHS (Y/C)
	• Audio: Stereo RCA audio input (L/R), and stereo mini-jack audio output
	• Cyclops 2050: Internal edge connector for Cyclops 2050 panel
	• Active-matrix color TFT (Thin Film Transistor)
Display Area	• 10.4 in. (264 mm) diagonal
	• 8.3 in. x 6.25 in. (211 mm x 158 mm)
Resolution	• 640 x 480 pixels
Number of Colors	• Up to 16.7 million
Response Time	• 30 to 50 milliseconds (typical)
Contrast Ratio	• 100:1 (typical)
Graphical User Interface	• Pull down menu system
	• LightBoard highlighting and annotating tools
LightBoard Highlighting Tools	• Line drawing in 8 colors
	• Selective erase
	• Clear all highlights
(Control devices include: Cyclops 2050, 100% Microsoft compatible serial mouse)	

User Interface Control Options	• Cyclops 2050 interactive pointer system
	• 100% Microsoft compatible serial mouse
	• Local front panel control
	• Programmable infrared remote
Power Requirements	• Auto switching from 90 to 270 VAC, 47 to 440 Hz
Approvals	• UL
	• CSA
	• GS (TÜV)
	• Dentori
	• SAA
	• SEMKO
	• NEMKO
	• DEMKO
	• SETI
Dimensions	• 15.0 in. (W) x 12.9 in (D) x 2.1 in. (H)
	• 381 mm (W) x 327.7 mm (D) x 53.3 mm (H)
Weight	• 6.5 lbs., (3.0 kg)
Warranty	• One year on parts and labor